

Universal-Ständerlochstanze 510-M Universal Punch with Stand 510-M

manuell / manual

Universelle 3 in 1 Ständerlochstanze zur Bearbeitung von Klemmenkästen, Montageplatten und Schaltschranktüren.

- Ideal zum Stanzen von Klemmenkästen, Gehäusen, Kabeleinführungsplatten und Schaltschranktüren aus Stahlblech oder Edelstahl bis 1000 x 2000 mm.
- Ausladung des Bügels: 510 mm
- Rund-, Quadrat-, Rechteck- sowie Locher in Sonderformen können eingesetzt werden
- aus Vollmaterial und spannungsfrei geglähter Stanzbügel, mit robustem Zahnstangenantrieb
- Bedienung mit Handhebel
- Einfacher und schneller Werkzeugwechsel
- Für Reihenstanzungen und Kleinserien
- Nibbeln bis 46,0 x 46,0 mm möglich

Maximale Blechstärken:

Stahl (ST37):	max. 2,0 mm
Rostfreier Stahl:	max. 1,5 mm (je nach Lochergröße)
Plastik, Polyester:	max. 4,0 mm (je nach Lochergröße)

Folgende Werkzeuge können eingesetzt werden:

Rundwerkzeuge	Ø 4,2 mm bis Ø 60,0 mm
Eckwerkzeuge	22,2 x 22,2 mm bis 46,0 x 46,0 mm
Schnittwerkzeuge	20,0 x 3,0 mm, 30,0 x 5,0 mm, 60,0 x 5,0 mm
SUB-MIN-D-Locher	9-polig bis 37-polig
Locher in Sonderformen	z.B. Ø 22,5 mm mit 4 Verdrehschutznasen 3,2 mm

Universal 3-in-1 tool for punching terminal boxes, mounting plates, and switch cabinet doors.

- Practically ideal for punching terminal boxes, housings, cable entry plates, and switch cabinet doors made of sheet steel or stainless steel up to 1000 x 2000 mm.
- Punching bow outreach: 510 mm
- For use of round punches, square punches, rectangular punches, and special punches
- Punching bow made of stress-relieved solid material, including rack drive
- Hand lever operation
- Easy and quick tool changing
- For in-line punching and small series
- Nibbling up to 46,0 x 46,0 mm

Maximum steel sheet thickness:

Steel (ST37):	max. 2,0 mm
Stainless steel:	max. 1,5 mm (according to punch size)
Plastics, polyester plastic:	max. 4,0 mm (according to punch size)

The following tools can be applied:

Round tools	Ø 4,2 mm up to Ø 60,0 mm
Angle-type tools	22,2 x 22,2 mm up to 46,0 x 46,0 mm
Cutting tools	20,0 x 3,0 mm, 30,0 x 5,0 mm, 60,0 x 5,0 mm
SUB-MIN-D-punches	9 pin up to 37 pin
Special punches	e.g. Ø 22,5 mm with 4 anti twist protection notches 3,2 mm



Bitte kontaktieren Sie uns für weitere Informationen zu diesem Produkt.
Please inquire for further information about this product